

CLICK[®] 4T SCOOTEX API SL

PRODUCT DATA SHEET

CLICK[®] 4T SCOOTEX SAE 10w30 API SL/MB is specially designed for automatic scooters and gearless 2-wheelers. Its exclusive and unique formulation does not let the oil film break easily, thereby providing superior protection even in heavy traffic 'stop-n-go' conditions. This leads to a distinctly superior performance, which can be felt from the first use itself.

FEATURES & BENEFITS

- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability.
- Active cleaning agents provide engine cleanliness.

APPLICATION

CLICK[®] 4T SCOOTEX SEA 10w30 API SL/MB grade is recommended for new generation Automatic bikes manufactured by most of the reputed manufactures like HERO MotorCorp, Baja Auto, Yamaha, Suzuki, TVS, Mahindra etc...

MEETS REQUIREMENTS OF

- API SL
- JASO MB

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Total Base #, mg/KOH/g	6.00
Viscosity Index	144
Flash Point, °C MAX	235
Pour Point, °C MAX	-42
TBN, mg KOH/gm	7.9

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541