

Tetra Gard

API GL-5 SAE 80W90

PRODUCT DATA SHEET

AUROLUBE'S TETRAGARD SAE 80W90 API GL-5 is high-tech gear oil, which is a thermally stable extreme pressure gear lubricant that offers outstanding protection. TetraGard SAE 80w90 transmission oils formulated with high-quality base oils combined with an effective phosphorus-Sulphur additive package. It comes with Good oxidation and thermal stability. It helps with outstanding viscosity-temperature behavior and the engine can be used all year round. The oil is suitable for hypoid axle drives with small or large axle offsets and synchronized manual transmissions. It gives excellent performance in all temperature conditions; hence it can be used for perfect all-seasons coverage. It meets and exceeds the performance requirements for API Services GL- 5 and MT-1. We recommend TetraGard SAE 80w90 for All hypoid differentials (conventional & limited slip) and manual transmission where an API GL- 5 or MT-1 is specified.

APPLICATIONS

Application areas are hypoid differential & drive axles and manual transmissions of automobiles. PERFORMANCE

BENEFITS

- Withstands severe temperatures and shock loading.
- Protect against wear and corrosion.
- Provides excellent anti-wear and anti-scuff protection.
- Good oxidation and thermal stability.
- Excellent performance in all temperature conditions, for perfect all-seasons coverage.

MEETS REQUIREMENTS OF

- API GL-5
- MIL-L 2105 D
- EP Type GL – 5 Level of IS: 1118:1992 (Re-affirmed 2011) specifications

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Kinematic Viscosity @ 100°C,cSt	13.6-16.5
Viscosity Index	100
Flash Point, °C MAX	200
Pour Point, °C MAX	-21

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541