

Turbo Charge

API - CH-4 SAE 15w40

PRODUCT DATA SHEET

TURBO CHARGE SAE 15W 40 API CH - 4 grade is a premium quality diesel engine oil made from the best paraffinic base stocks and state of art additive technology, specially developed for heavy commercial vehicles and Passenger cars running on HSD. The product has been designed to address the operational severity and engine durability issues of these diesel engines.

TURBO CHARGE 15W 40 provides optimum protection for control of corrosive wear, low and high temperature stability, soot handling properties, piston deposit control, valve train wear, oxidative thickening, foaming and viscosity loss due to shear.

APPLICATIONS

TURBO CHARGE 15W 40 grade is recommended for new generation diesel engines of heavy commercial, light commercial vehicles, multi utility vehicles employing Euro III/II technologies like Turbocharging and CRDI etc. It is also suitable for construction equipment & DG sets as well as passenger cars requiring high quality engine oils.

FEATURES & BENEFITS

- Protects engine from excessive wear.
- Longer life for cylinder liner, piston ring, valves, cam.
- Longer oil life due to excellent viscosity control.
- Higher levels of engine cleanliness.
- Helps to reduce pollution

MEETS REQUIREMENTS OF

- | | | |
|-------------------|-----------------|--------------------|
| • API CH-4 / CG-4 | • VOLVO VDS-2 | • ACEA A3/B3/E5-02 |
| • Mack EO-M Plus | • MB 228.3 | • MAN M3275 |
| • MTU Type 2 | • Cummins 20076 | • TML's SS 6571 |

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Kinematic Viscosity @ 100°C, cSt	14-15
Viscosity Index	138
Flash Point, °C MAX	230
Pour Point, °C MAX	-27
TBN, mg KOH/gm	9.7

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541