



PRODUCT DATA SHEET

ATF Plus is a high quality automatic transmission fluid manufactured from highly refined base stocks and carefully selected additives, to provide a superior performance in the automatic transmission systems of automotive.

ATF Plus provides superior protection for the automatic transmission system against wear & corrosion, while its high viscosity index ensures unmatched lubrication at high operating temperatures.

APPLICATIONS

ATF Plus is recommended for automatic transmissions and power steering systems of vehicles requiring general motors "TYPE A SUFFIX A" quality fluids.

It is also recommended for synchromesh gear boxes and certain manual transmissions, torque converters and hydraulic systems, where such types of fluids are specified.

FEATURES & BENEFITS

Superior oxidation and thermal stability reduces deposit formation • Superior anti-wear protection to critical parts • Very high viscosity index and low pour point ensures proper lubrication in both high temperature operation & low starting temperatures • Good shear stability implies a longer service life of oil and the hardware • Good foam control leads to smooth gear shifting • Compatible with all common elastomers • Provides good protection against rust and corrosion

MEETS REQUIREMENTS OF

General Motors Type A Suffix A

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Kinematic Viscosity @ 100°C,cSt	7.3
Viscosity Index	151
Flash Point, °C MAX	212
Pour Point, °C MAX	-35
CU-Strip Corrosion, 100 °C, 3hrs, Max	1

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541