

PUMP SET OIL

PRODUCT DATA SHEET

AUROLUBE PUMP SET OIL, SAE 20W40 API CD/SF is formulated with high performing anti-wear additive which results in a reduction of engine internal frictions thereby increases life span and duration of the internal pump components for better durability and performance. This allows the pump to work longer hours while avoiding the most common problem of oil thickening that directly affects satisfactory performance. The superior additive chemistry ensures better ignition at low ambient temperature as it has been specially formulated for better engine cleanliness and oxidation stability. An all-season oil specially designed to retain a high level of alkalinity during use acting as an excellent dispersing agent to minimize soot-induced oil thickening and associated engine wear and tear. Its high disparity and enhance formula keep oil thickening in checks and helps prolong the oil drain intervals.

FEATURES & BENEFITS

- It helps with a Longer drain period.
- It gives Extended engine life.
- It is a special formulation to enhance power and protection at a high temp.
- Excellent Oxidations stability
- Excellent overall performance in different engine design Engine Oil
- Reduce soot induced oil thickening and the related engine put on.

MEETS REQUIREMENTS OF

- Meets the performance benchmarks of API CD/SF

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Kinematic Viscosity @ 100°C,cSt	13.5-16
Viscosity Index	110
Flash Point, °C MAX	200
Pour Point, °C MAX	-12
TBN, mg KOH/gm	4.20

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541