



PRODUCT DATA SHEET

SYNGARD 75W90API GL-5 is a proven synthetic product that outperformance conventional, extreme-pressure type gear lubricants in both conventional & limited slip applications & helps provide. It is excellent aging resistance, good viscosity, or temperature properties. It has a very good corrosion protection and good tolerability to non-ferrous metal. Also, it helps to Reduce transmission noise, wide viscosity range. It comes with A high oxidative stability to prevent oil thickening and deposits as well as has an excellent cold flow property. AUROLUBE SynGard 75w90 meets or exceeds the performance requirements of API GL-5. For Outstanding protection of hybrid differentials where an API GL-5 quality 75w90 oil is recommended.

FEATURES & BENEFITS

- Outstanding protection of hybrid differentials where an API GL-5 quality 75w90 oil is recommended.
- Minimal war & spalling under high-speed, high torque & high-horsepower conditions, exceptional resistance to oil breakdown from heat & extended high speed operations.
- Decrease transmission noise, wide viscosity range
- Outstanding cold temperature performance.
- Gear shifting ease & reduction of chatter.
- It is perfectly designed for good seal compatibility
- Less frictions which help to lower operating temperatures.

MEETS REQUIREMENTS OF

- API GL-5
- API MT-1

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Properties	Value
Kinematic Viscosity @ 100°C,cSt	15.7
Viscosity Index	144
Flash Point, °C MAX	210
Pour Point, °C MAX	-40

SRI AUROBINDO LUBES PRIVATE LIMITED

Regd Office : 29, 3rd Floor, C Wing, Durian Estate, Goregaon-Mulund Link Road, Goregaon (East), Mumbai - 400063

Customer Care: 022-40037181 Email: sales@aurolube.com Website: www.aurolube.com

CIN NO. U51909MH2007PTC172541